

Ideal BarTap®

High Flow (HF) or Eco Flow (EF)

IBT-D-PSS-HF
IBT-D-PSS-EF

IBT-D-MSS-HF
IBT-D-MSS-EF

IBT-D-GSS-HF
IBT-D-GSS-EF

IBT-D-BSS-HF
IBT-D-BSS-EF

IBT-D-YSS-HF
IBT-D-YSS-EF

IBT-D-RSS-HF
IBT-D-RSS-EF



Polished
Stainless Steel



Matte
Stainless Steel



PVD Gun Metal Gray™
Stainless Steel



PVD Satin Black
Stainless Steel



PVD Brushed Gold
Stainless Steel
Limited Edition



PVD Polished Rose Gold
Stainless Steel
Limited Edition

Specifications

- Single-lever control
- Ceramic disk cartridge
- Forward rotating COMFORTFEEL™ lever handle
- Q-Dock™ docking system holds hand spray in place
- Ergonomic slide switch to select Ideal Flow, Laminar or Spray Flow
- Automatic return to laminar flow
- Concealed easy clean spray face
- Spout rotates 360°
- Counterweight
- Dual check valves
- 24" stainless steel flexible hoses 3/8" compression
- Maximum counter thickness 2"
- Minimum install hole diameter 1 3/8"
- Optional base ring included
- Total height 15 13/16"
- High Flow 2.2 GPM maximum flow rate
- Eco Flow 1.8 GPM maximum flow rate
- For use with Water Filtration System* (not included)

*Note: May reduce water flow

Construction

Solid 316L machined stainless steel construction
Available in Polished, Matte, PVD Gun Metal Gray™, PVD Satin Black, PVD Brushed Gold, PVD Polished Rose Gold
Indoor & outdoor
Limited Lifetime Warranty
Made in Italy

Codes/Standards

ASME 112.18.1
CSA B125.1
NSF 61, 372
CALGreen
UPC
NPC
ADA

