

# Ideal BarTap®

High Flow (HF) or Eco Flow (EF)

IBT-D-PSS-HF  
IBT-D-PSS-EF

IBT-D-MSS-HF  
IBT-D-MSS-EF

IBT-D-GSS-HF  
IBT-D-GSS-EF

IBT-D-BSS-HF  
IBT-D-BSS-EF

IBT-D-YSS-HF  
IBT-D-YSS-EF

IBT-D-RSS-HF  
IBT-D-RSS-EF



Polished  
Stainless Steel



Matte  
Stainless Steel



PVD Gun Metal Gray™  
Stainless Steel



PVD Satin Black  
Stainless Steel



PVD Brushed Gold  
Stainless Steel  
*Limited Edition*



PVD Polished Rose Gold  
Stainless Steel  
*Limited Edition*

## Specifications

- Single-lever control
- Ceramic disk cartridge
- Forward rotating COMFORTFEEL™ lever handle
- Q-Dock™ docking system holds hand spray in place
- Ergonomic slide switch to select Ideal Flow, Laminar or Spray Flow
- Automatic return to laminar flow
- Concealed easy clean spray face
- Spout rotates 360°
- Counterweight
- Dual check valves
- 24" stainless steel flexible hoses 3/8" compression
- Maximum counter thickness 2"
- Minimum install hole diameter 1 3/8"
- Optional base ring included
- Total height 15 13/16"
- High Flow 2.2 GPM maximum flow rate
- Eco Flow 1.8 GPM maximum flow rate
- For use with Water Filtration System\* (not included)

\*Note: May reduce water flow

## Construction

Solid 316L machined stainless steel construction  
Available in Polished, Matte, PVD Gun Metal Gray™, PVD Satin Black, PVD Brushed Gold, PVD Polished Rose Gold  
Indoor & outdoor  
Limited Lifetime Warranty  
Made in Italy

## Codes/Standards

ASME 112.18.1  
CSA B125.1  
NSF 61, 372  
CALGreen  
cUPC  
ADA

