Ideal BarTap. with Filtration

High Flow (HF) or Eco Flow (EF)



Specifications

Ideal BarTap Single-lever control Ceramic disk cartridge Forward rotating COMFORTFEEL[™] lever handle Q-Dock[™] docking system holds hand spray in place Ergonomic slide switch to select Ideal Flow, Laminar or Spray Flow Automatic return to laminar flow Concealed easy clean spray face Spout rotates 360° Counterweight Dual check valves 24" stainless steel flexible hoses 3/8" compression Maximum counter thickness 2" Minimum install hole diameter 1 3/8" Optional base ring included Total height 15 13/16" High Flow 2.2 GPM maximum flow rate Eco Flow 1.8 GPM maximum flow rate For use with Water Filtration System* (included)



(Included) Water Filtration System Service flow rate 2.0 gpm Rated capacity 7,900 gallons Operating pressure 10 - 125 psi Operating temperature 35 - 100°F Overall dimensions 16 7/8" x 4 1/8" Reduces lead, chlorine, cysts and other contaminants Quick twist-lock cartridge replacement Replacement filter cartridge dimensions 14 1/2" x 3" Internal parts never exposed to human handling Filtration protects capital equipment from early breakdown Installs vertically (allow 2 1/2" clearance) Parts Included: Mounting bracket and screws, plastic tubing, push-fit Tee

Construction

Ideal BarTap

Solid 316L machined stainless steel construction Available in Polished, Matte, PVD Gun Metal Gray™, PVD Satin Black, PVD Brushed Gold, PVD Polished Rose Gold Indoor & outdoor Limited Lifetime Warranty Made in Italy

Water Filtration System

Five Year Warranty Made in the USA

Codes/Standards

Ideal BarTap ASME 112.18.1 CSA B125.1 NSF 61, 372 CALGreen cUPC ADA

Water Filtration System

IAPMO Certified NSF/ANSI 42, 53, 372

