

Ideal Tap

High Flow (HF) or Eco Flow (EF)



Specifications

- Single-lever control ceramic disk cartridge
 - Forward rotating COMFORTFEEL™ lever handle
 - 11" CENTERSTATION™ spout projection
 - 11" Pot fill height from deck to spout outlet
 - Hand spray extends up to 26" from spout
 - Q-Dock™ docking system holds hand spray in place
 - Ergonomic slide switch to select Ideal Flow. Laminar or Spray Flow
 - Automatic return to laminar flow
 - Concealed easy clean spray face
 - Spout rotates 360°
 - Quiet, smooth gliding hose
 - Counterweight
 - Dual check valves
 - 24" stainless steel flexible hoses 3/8" compression
 - Maximum counter thickness 2"
 - Minimum install hole diameter 1 3/8"
 - Optional base ring included
 - Total height 21 1/4"
 - High Flow 2.2 GPM maximum flow rate
 - Eco Flow 1.8 GPM maximum flow rate
 - For use with Water Filtration System* (not included)
- *Note: May reduce water flow

Construction

- Solid 316L machined stainless steel construction
- Available in Polished, Matte, PVD Gun Metal Gray™, PVD Satin Black, PVD Brushed Gold, PVD Polished Rose Gold
- Indoor & outdoor
- Limited Lifetime Warranty
- Made in Italy

Codes/Standards

- ASME 112.18.1
- CSA B125.1
- NSF 61, 372
- CALGreen
- cUPC
- ADA

