Ideal WashStation[™] 30S **SPECIFICATIONS**





IWA-30-S-GT



IWA-30-S-BA



IWA-30-S-GR



IWA-30-S-WH



Wash Tools included (WKT-4T)



(1) Lower Tier (1) Upper Tier Wash Bowl 12" x 17" Utensil Caddy 6" x 18 UC-06-U-xx WB-12-L-xx









Specifications


Single bowl Users: 1 Wash Tools included: Four Galley BarTap. recommended: One Outside dimensions: 27 1/2" x 19 1/2" x 10 5/16" Interior dimensions: 26" x 17" x 10" Countertop cutout: 26 1/2" x 18" Basin area: 26" x 16" Minimum cabinet size: 30" or 76cm

Basin (KSO-30-S-SS)

16GA 316L stainless steel indoor/outdoor SilentArmor[™] sound reduction technology Angel finish Three tier design Star™ groove pattern Reversible side drain Drain cover included Limited Lifetime Warranty Made in the USA ASME A112.19.3/CSA B45.4 certified cUPC™ certified








Ideal WashStationTM 30S SPECIFICATIONS | Right Hand Drain Orientation



Tap Hole Specifications




SUGGESTED GALLEY TAP PLACEMENT GUIDE


Suggested maximum inside corner radius of counterlop cutout 3/8" () Galley BarTap- 1 3/8" min to 1 1/2" max hole diameter Center Tap hole diameters 2" behind cutout Note: Galley Hot & Cold Tap requires a minimum 8" clearance to center if installed to the right of the Galley Tap


Note: Galley Hot & Color hap requires a minimum 8' clearance to center in installed to the right of the Galley hap Note: Tap Placements are for right hand or left hand drain orientation

Call 800.375.4255 or email customercare@thegalley.com for additional guidance on Tap and Tap Accessory placements



Countertop Cutout Plan





STAINLESS STEEL COMPLIANCE ASME A112. 19.3-2008/CSA B45.4-08


WE RESERVE THE RIGHT TO MAKE REVISIONS WITHOUT NOTICE IN THE DESIGN OF PRODUCTS OR IN PACKAGING UNLESS THIS RIGHT HAS SPECIFICALLY BEEN WAIVED AT THE TIME THE ORDER IS ACCEPTED.

DWG and DXF templates available on our website: TheGalley.com/specification-library

Questions? For additional assistance, please contact The Galley's Customer Care Department at 800.375.4255 Ideal WashStationTM 30S SPECIFICATIONS | Left Hand Drain Orientation




Tap Hole Specifications





SUGGESTED GALLEY TAP PLACEMENT GUIDE Suggested maximum inside corner radius of countertop cutout 3/8" ⁽⁶⁾ Galley Tap 13/8" min to 1 1/2" max hole diameter Center Tap hole diameters 2" behind cutout Note: Salley Hot & Cold Tap requires a minimum 8" clearance to center if installed to the right of the Galley Tap Note: Tap Placements are for right hand or left hand drain orientation

Call 800.375.4255 or email customercare@thegalley.com for additional guidance on Tap and Tap Accessory placements



Countertop Cutout Plan





STAINLESS STEEL COMPLIANCE ASME A112. 19.3-2008/CSA B45.4-08

WE RESERVE THE RIGHT TO MAKE REVISIONS WITHOUT NOTICE IN THE DESIGN OF PRODUCTS OR IN PACKAGING UNLESS THIS RIGHT HAS SPECIFICALLY BEEN WAIVED AT THE TIME THE ORDER IS ACCEPTED.

DWG and DXF templates available on our website: TheGalley.com/specification-library

Questions? For additional assistance, please contact The Galley's Customer Care Department at 800.375.4255