


IWA² 4S + DryDock 12

SPECIFICATIONS

THE GALLEY®

IWA-4-S-DD-12-S-2-QW



Quartered White Oak / Exclusive Gray Resin+

IWA-4-S-DD-12-S-2-WA



American Black Walnut / Graphite Resin+

IWA-4-S-DD-12-S-2-GT



Graphite Wood Composite / Graphite Resin+

IWA-4-S-DD-12-S-2-GR



Exclusive Gray Resin+ / Resin+

IWA-4-S-DD-12-S-2-WH



Designer White Resin+ / Resin+

Wash Tools included (WKT-4T)




Specifications


Single bowl
Users: 1
Wash Tools included: Four
DryDock Tool included: One
Galley Tap recommended: One
Outside dimensions: 57 1/2" x 19 1/2" x 2 7/8"
Interior dimensions: 56" x 18" x 2 3/4"
Countertop cutout: 56" x 18"
Minimum cabinet size: 60" or 150cm
Minimum clearance required for DryDock below countertop: 3"
DryDock location: Drain side (S)

Basin (KSO-4-S-DS-12-S-2-SS)

16GA 316L stainless steel indoor/outdoor
SilentArmor™ sound reduction technology
Angel finish
Three tier design with integrated Upper Tier
Star™ groove pattern
Reversible side drain
Drain cover included
Limited Lifetime Warranty
Made in the USA
ASME A112.19.3/CSA B45.4 certified
cUPC™ certified



Center Galley Tap holes 2" from the back of the 18" countertop cutout



Important Installation Note: DryDock requires 3" minimum clearance below countertop

Customize Your Galley

Add 7-12" length
Add 1-6" length
Add 18" DryDock
Add 12" DryDock
Apron front


9" depth
Center drain
WorkTop™
*Color coded labels available

DryDock Tool included (DR-12)



Upper Deck® & citrine.

Cover set UD-4-12-3P-QW/WA/GT/GR/WH White Oak, Walnut, Graphite, Gray or White Resin




citrine care



Recommended Basin Accessories & G4

Bottom Grate set BG-4-S-2-SS Stainless Steel



Strainer M-DRN-MSS
Angel Finish 304 Stainless Steel



Disposer Strainer G-DRN-MSS
Angel Finish 304 Stainless Steel



Auto Strainer A-DRN-PSS/MSS/BSS/YSS
Angel Finish 304 Stainless Steel with Polished, Matte, PVD Satin Black, or PVD Brushed Gold knob



Disposal G4-WD-125




IWA² 4S + DryDock. 12

SPECIFICATIONS | Right Hand Drain Orientation

THE GALLEY®

Tap Hole Specifications



SUGGESTED GALLEY TAP PLACEMENT GUIDE

Suggested maximum inside corner radius of countertop cutout 3/8"


① Galley Tap 1 3/8" min to 1 1/2" max hole diameter

Center Tap hole diameters 2" behind cutout

Note: Galley Hot & Cold Tap requires a minimum 8" clearance to center if installed to the right of the Galley Tap



Note: Tap Placements are for right hand or left hand drain orientation

Call 800.375.4255 or email customercare@thegalley.com for additional guidance on Tap and Tap Accessory placements



Countertop Cutout Plan

Important Installation Note: DryDock requires 3" minimum clearance below countertop



STAINLESS STEEL COMPLIANCE ASME A112. 19.3-2008/CSA B45.4-08

WE RESERVE THE RIGHT TO MAKE REVISIONS WITHOUT NOTICE IN THE DESIGN OF PRODUCTS OR IN PACKAGING UNLESS THIS RIGHT HAS SPECIFICALLY BEEN WAIVED AT THE TIME THE ORDER IS ACCEPTED.


DWG and DXF templates available on our website:

TheGalley.com/specification-library

Questions? For additional assistance, please contact
The Galley's Customer Care Department at 800.375.4255

THE GALLEY®



Technical drawing of a rectangular cutout with a central circular feature. The drawing shows a rectangular frame with a central circle containing a crosshair. Dimensions are provided for the overall size, cutout size, and internal features. The overall dimensions are 57 1/2 inches wide and 19 1/2 inches high. The cutout dimensions are 56 inches wide and 18 inches high. The internal dimensions are 44 inches wide and 12 inches high. The central circle has a diameter of 8 inches. The frame has a thickness of 3/4 inch (19 mm). The cutout has a depth of 8 inches. The internal dimensions are 44 inches wide and 12 inches high. The central circle has a diameter of 8 inches. The frame has a thickness of 3/4 inch (19 mm). The cutout has a depth of 8 inches.



Note: Tap Placements are for right hand or left hand drain orientation

Call 800.375.4255 or email customer care@thegalley.com
for additional guidance on Tap and Tap Accessory placements

Important Installation Note: DryDock requires 3" minimum clearance below countertop



*Questions? For additional assistance, please contact
The Galley's Customer Care Department at 800.375.4255*