

# Ideal Tap

High Flow (HF) or Eco Flow (EF)

IWT-D-PSS-HF  
IWT-D-PSS-EF

IWT-D-MSS-HF  
IWT-D-MSS-EF

IWT-D-GSS-HF  
IWT-D-GSS-EF

IWT-D-BSS-HF  
IWT-D-BSS-EF

IWT-D-YSS-HF  
IWT-D-YSS-EF

IWT-D-RSS-HF  
IWT-D-RSS-EF



## Specifications

- Single-lever control ceramic disk cartridge
- Forward rotating COMFORTFEEL™ lever handle
- 11" CENTERSTATION™ spout projection
- 11" Pot fill height from deck to spout outlet
- Hand spray extends up to 26" from spout
- Q-Dock™ docking system holds hand spray in place
- Ergonomic slide switch to select Ideal Flow. Laminar or Spray Flow
- Automatic return to laminar flow
- Concealed easy clean spray face
- Spout rotates 360°
- Quiet, smooth gliding hose
- Counterweight
- Dual check valves
- 24" stainless steel flexible hoses 3/8" compression
- Maximum counter thickness 2"
- Minimum install hole diameter 1 3/8"
- Optional base ring included
- Total height 21 1/4"
- High Flow 2.2 GPM maximum flow rate
- Eco Flow 1.8 GPM maximum flow rate
- For use with Water Filtration System\* (not included)
- \*Note: May reduce water flow

## Construction

- Solid 316L machined stainless steel construction
- Available in Polished, Matte, PVD Gun Metal Gray™, PVD Satin Black, PVD Brushed Gold, PVD Polished Rose Gold
- Indoor & outdoor
- Limited Lifetime Warranty
- Made in Italy

## Codes/Standards

- ASME 112.18.1
- CSA B125.1
- NSF 61, 372
- CALGreen
- UPC
- NPC
- ADA

